

# WEBEL TECHNOLOGY LIMITED

## CORRIGENDUM - I

**Tender No. WTL/PSC/LAN/19-20/032 dated 04.02.2020**

Sl. No.	Section	Clause No.	Page No.	Present Entry	Replace with
1	D	13	10	<p><b>CONTRACT EXECUTION</b> On receipt of the Letter of Award the contractor should submit a Performance Bank Guarantee (PBG) equivalent to 10% of the total contract value within three weeks from the date of receipt of Letter of Award/Order. The PBG should be valid for six months more than the warranty period. All delivery of the material will have to be completed within 45 days from the date of acceptance of contract and the contractor has to ensure all activities leading to the commissioning of the contract to be completed within 90 days from the date of award. Subsequent to the award of contract, the contractor will have to arrange for the requisite material as per BOM.</p>	<p><b>CONTRACT EXECUTION</b> On receipt of the Letter of Award the contractor should submit a Performance Bank Guarantee (PBG) equivalent to 10% of the total contract value within three weeks from the date of receipt of Letter of Award/Order. The PBG should be valid for six months more than the warranty period. All delivery of the material will have to be completed within 45 days from the date of acceptance of contract and the contractor has to ensure all activities leading to the commissioning of the contract to be completed within <b>45 days</b> from the date of award. Subsequent to the award of contract, the contractor will have to arrange for the requisite material as per BOM.</p>
2	D	1	8	<p><b>"Period of Agreement"</b> means 5 years from the date of Final acceptance of the Project.</p>	<p><b>"Period of Agreement"</b> means <b>3 years</b> from the date of Final acceptance of the Project.</p>
3	I	Technical specification	30	<p><b>(Minimum Specification of 24 port L2 PoE Ethernet Switch)</b> Sl. No.: 12 Switch should support network segmentation that overcomes the limitation of VLANs using VXLAN and VRFs.</p>	<p><b>(Minimum Specification of 24 port L2 PoE Ethernet Switch)</b> Sl. No.: 12 Switch should support network segmentation that overcomes the limitation of VLANs <b>using VXLAN or VRFs.</b></p>
4	I	Technical specification	30	<p><b>(Minimum Specification of 24 port L2 PoE Ethernet Switch)</b> Sl. No.3: Switch should have minimum 2 GB RAM and 2 GB Flash.</p>	<p><b>(Minimum Specification of 24 port L2 PoE Ethernet Switch)</b> Sl. No.3: Switch should have minimum 2 GB RAM and <b>1 GB Flash.</b></p>
5	I	Technical specification	26	<p><b>(Minimum Specification of Wireless Controller)</b> Sl. No 20: WLC should support PMIPv6 and EoGRE tunnels on northbound interface</p>	<p><b>(Minimum Specification of Wireless Controller)</b> Sl. No 20: WLC should support PMIPv6 <b>OR</b> EoGRE tunnels on northbound interface</p>
6	I	Technical specification	26	<p><b>(Minimum Specification of Wireless Controller)</b> Sl. No 27: Should able to do dynamic channel bonding based on interference detected on particular channel.</p>	<p><b>Minimum Specification of Wireless Controller)</b> Sl. No 27: Should able to do channel bonding based on interference detected on particular channel.</p>
7	I	Technical specification	28	<p><b>Minimum Specification of Unified Wireless Access points (Indoor)</b> Sl. No 1: Must support 4x4 MIMO for both 802.11ac and 802.11n client</p>	<p><b>Minimum Specification of Unified Wireless Access points (Indoor)</b> Sl. No 1: Must support <b>4x4 :4SS MIMO</b> for both 802.11ac and 802.11n client</p>